

# RD MARK<sup>TM</sup>

An ISO 9001: 2008 Certified Company

# RD MARK<sup>TM</sup>

An ISO 9001: 2008 Certified Company



*A New Generation*  
**LUBRICANTS & GREASES**

## OUR INDUSTRIAL PRODUCTS

### INDUSTRIAL PRODUCTS

RD MARK Hydraulic Oils  
32, 46, 68, 100, 150, 220, 320, 460  
Compressor oil  
Neat Cutting oil  
Pneumatic oil  
RD MARK Industrial Greases  
RD MARK Spin oils 5, 12, 22  
RD MARK Synth Cut  
RD MARK Quench Spl. oil  
RD MARK Quench 32 Hs oil  
RD MARK Therm Spl. oil  
RD MARK Therm 500, 600 oil  
RD MARK Line oil 68, 100, 150, 220  
RD MARK Hone oil  
RD MARK Rubber Processing oil 541  
RD MARK Orchard Spray oil  
Available Packs : 20 & 210 Ltrs.

### RECOMMENDED FOR

Circulating & Hydraulic oil  
Air Press 150/220  
Neat cutting oil  
Pneumatic oil  
Lithium base EP-003  
Spindle oil  
Synthetic cutting oil  
Quenching oil  
Quenching oil  
Heat Transfer fluid  
Heat Transfer fluid  
Machinery oil  
Honning oil

Marketed by:  
**RD MARK LUBRICANTS**



Mfd. & Pkd. by:  
**FUEL STRAINERS (INDIA)**  
B-169, DSIHDC, BAWANA  
Customer Care +91 9855441816  
rdmark29@yahoo.com



**AUTOMOTIVE OIL, INDUSTRIAL OIL & GREASES**



## MULTIGRADE 20W40

Multigrade Engine Oil 20W40 is suitable for medium and heavy duty engines LCV, VAN and stationary engines. It ensures lower maintenance cost, maximises engine life and ease in cold starting.

SPECIFICATIONS		API CF-4
Sr.	Properties	Multigrade 20W40
1	Kinematic Viscosity, cSt@100°C	13-16
2	Viscosity Index	220
3	Pour Point	-9
4	Flash Point, COC, °C	220
5	TBN mg KOH / gm	5-7



AVAILABLE IN : 500ml., 1Ltr., 3Ltr., 5Ltr., 7.5Ltr., 10Ltr., 20Ltr., 50Ltr., 210Ltr.



AVAILABLE IN : 500ml., 1Ltr., 5Ltr., 10Ltr., 20Ltr., 26Ltr., 50Ltr., 210Ltr.

## GEAR OIL EP-90

GEAR OIL EP-90/140 multipurpose extreme pressure lubricants formulated from high viscosity. India base oil and further fortified with complete package. Anti corrosion, Anti rust, Anti friction properties. Excellent wear protection of gear teeth. Excellent oxidation resistance & thermal stability.

API GL-4		SPECIFICATIONS
Sr.	Properties	GEAR OIL EP-90
1	Kinematic Viscosity, cSt@100°C	28-32
2	Viscosity Index	90
3	Pour Point	-6
4	Flash Point, COC, °C	240

## TURBO 15W40

15W40 Multigrade Engine oil formulated with new technology highly performance additives. Anti corrosion, Anti from, Anti wear very high thermal & oxidation stability. Quick Starting in all season. Reduced Exhaust Emission compatible catalytic converter. Diesel engine also applicable to passenger Car, Commercial vehicle recommended to latest model cars & Trucks.

API CH-4		SPECIFICATIONS
Sr.	Properties	(Power Plus) 15W40
1	Kinematic Viscosity, cSt@100°C	13-16
2	Viscosity Index	135
3	Pour Point	-21
4	Flash Point, COC, °C	220
5	TBN mg KOH / gm	8-10



AVAILABLE IN : 1Ltr., 3Ltr., 3.5Ltr., 5Ltr., 7.5Ltr., 10Ltr., 15Ltr., 20Ltr., 50Ltr., 210Ltr.

## PUMP SET OIL

PSO SAE-40 is dedicated engine oil for agricultural diesel pump set oil. It is specially made from petroleum mineral oil.

Ensure system cleanliness & economical. Reduces oil top-up. Prevent from corrosion & rust.

SPECIFICATIONS		API CD
Sr.	PROPERTIES	PUMP SET OIL SAE-40 GRADE
1	V.I. (min)	95
2	Kin Viscosity, cSt@100°C	13.5-15.5
3	Flash Point, (COC)°C, min	220
4	TBN mg KOH / gm	8.0-10.0



AVAILABLE IN : 1200ML, 1.5Ltr., 2Ltr., 3.5Ltr., 5Ltr., 50Ltr., 205Ltr.

## 4 STROKE OIL 20W40

4T oil is a premium quality engine oil formulated to high performance four stokes engine oils in 2 wheelers, motorcycle & scooter. This gives full protection over rust, wear & tear. Oil is catalytic converter compatible. High fuel efficiency. Excellent load carrying capacity. Protect engine from wear & corrosion.

SPECIFICATIONS		API SL / JASO MA-2
Sr.	PROPERTIES	4T OIL 20W40 GRADE
1	V.I. (min)	110
2	Kin Viscosity, cSt@100°C	13.5-15.5
3	Flash Point, (COC)°C, min	210
4	TBN mg KOH / gm	8.0-10.0
5	Pour Point °C, max	(-) 21



AVAILABLE IN : 500ml., 900ml., 1Ltr., 20Ltr., 50Ltr., 210Ltr.



AVAILABLE IN : 100 gms., 200 gms., 500 gms., 1 kg., 2 kg., 3 kg., 5kg., 10kg., 18 kg., 180 kg.

## AP-LR GREASE

APLR is a blend of lithium and advanced chemistry products of international quality and wide spectrum manufactured with various premium quality additives like anti rust, anti-wear compounds, hydroxyl serrate soap and solvent refined high viscosity index paraffinic base fortified with EP additive. It is specially formulated to enhance re-lubrication interval, in ideal conditions upto 40000 kms. It has good thermal, chemical and structural stability.

NLGI-3		SPECIFICATIONS
Sr.	Properties	AP-LR GREASE
	NLGI-3	3
1	Consistency of worked grease at 25±0.5°C	220-250
2	Drop Point, °C Min.	184
3	Soap Type Structure	Lithium Smooth & Buttery